T&S BRASS AND E			Mode	el No.	
2 Saddleback	Cove / P.O. Box 1088 Rest, SC 29690	9, INC.	L) E	C-3100-LN	
	,	REG. #/ ISO #9		No.	
Travelers Rest, SC: 800-476-4103 Simi Valley, CA: 800	-423-0150 Fax: 864-834-	3518 www.tsbrass.c	com		
This Space for Architect/Engineer Approval					
Job NameDate	6.	Ø1" [25mı	m]		
Model Specified Quantity	ADA Compliant	Thru—			
Customer/Wholesaler					
Contractor ChekPoint"					
Architect/Engineer		ϕ 5/32" [4mm]	[2	1" 5mm]	
3 5/8" x 4 3/16" x 2" Deep		Mounting		atail	
[92mm x 106mm x 51mm]				- <u> </u>	
Waterproof Control Module Box (Blue) w/ Internal Flow Control Setting Switches,					
AC or DC operated w/ (4) AA Batt					
		2 1/	/4"		
24" [610mm]		[58n	nm]		
Sensor Cable Removeab	le /				
Strainer				_	
Starv					
DECK					
Ø 1/8" [3mm]					
2 1/4 Max. / Pin installed					
for Anti-rotation feature. Remove					
1/2" NRSM x 1/4" NRSM					
18" [457mm] Long Flexible (See Mounting Hole Detail)					
St. Šteel Hose (1)					
100-135 VAC Adapter					
w/ 144" [3658mm] Long Power Cord.					
(Remove Rubber Plugs					
	on Module and to Connect)	Cable			
	,				
Temperature Mixing Value	-Furnished w/ (2)		-		
Mixing Valve – 3/8" Compression x 1/2" NPSM 18" [457mm] Flex. St. Steel Supply Hose					
NOTE: Supply Stops by Others			Checked	Approved	
Product Specifications: Chrome Plated Brass Deck Mount (Less Gooseneck and Ae		GEF	JRM	Approved JHB	
Control Module with Internal Flow Control Setting Switches		Date:			
Temperature Control Mixing Valve, 18" Long Hot & Cold		ſS	09/11/08		
Supply Stop Flexible Connector Hoses			Sheet: 1 of 2		



T&S BRASS AND BRONZE WORKS, INC.

2 Saddleback Cove / P.O. Box 1088

Travelers Rest, SC 29690



Model No.

EC-3100-LN

REG. #A2601 Item No.

Travelers Rest, SC: 800-476-4103 Simi Valley, CA: 800-423-0150 Fax: 864-834-3518 www.tsbrass.com

ľ

(5)

ITEM	SALES	DESCRIPTION	
NO.	NUMBER		
1	017195-45	Angled Sensor w/ Cable	
2	016297-45	Inlet Hose, Faucet, 1/2" NPSM-F x 1/4" NPSM-F	
3	016647-45	ChekPoint Electronic Module (Blue)	
4	5EF-0002	A/C Transformer	
5	5EF-0006	Manual Mixing Valve	
6	5EF-0005	Supply Hose, 9/16-24 Female x 1/2" NPSM	

Label for Flow Control Switch Settings is located on Inside of Back Cover.

Flow Control Switches are located inside Module Housing in Black Box next to Battery Compartment. *Switches are set to DEFAULT position: Auto Time Out = 10 seconds Shut Off Delay = 1 second.

Remove (4) screws and back cover to access switches.

(6) Auto Time Out Selections - 10 sec, 25 sec, 45 sec, 60 sec, 3 min, 20 min (6) Shut Off Delay Selections - 1 sec, 2 sec, 3 sec, 4 sec, 5 sec, 6 sec Product Specifications: Chrome Plated Brass Electronic Faucet: Drawn Approved Checked Deck Mount (Less Gooseneck and Aerator), AC/DC GEF JHB JRM Control Module with Internal Flow Control Setting Switches, Scale: Date: Temperature Control Mixing Valve, 18" Long Hot & Cold NTS 09/11/08 Supply Stop Flexible Connector Hoses Sheet: 2 of 2

*Available Water Flow Control Selections:

6)